



## 40.101N | Total Block-Out

### Total Glass | White Printable Media

#### Features

40.101N | Total Block-Out is a 200 micron dual-layered PVC, providing 100% opacity. This product has a gloss white face film and is printable with the full range of printing methods: (eco)solvent, UV and latex inks. Total Block-out also gives good results with screen printing inks.

Providing total opacity, 40.101N is the ideal solution for double-sided graphics for retail window applications, without grey adhesives visible on the backside. Total Block-out is a 200 micron vinyl, which makes the application user-friendly and swift.

In order to achieve a perfect match for double-sided window applications, **we recommend to combine** the 40.101N Total Block-Out **with our 50.001N Crystal Clear**.

#### Technical & Performance Information

Film Thickness	200 micron
Adhesive Thickness	25 micron
Total Thickness	225 micron
Adhesive Type	Removable Clear Solvent based Acrylic
Release Liner	140 gsm kraft liner
Artificial Weathering *	3 years
Adhesion to steel (20 mins / 180°)	12 N/25 mm
Adhesion to steel (24 hrs / 180°)	17 N/25mm
Dimensional Stability	Good
Application Temperature	+ 5 to +25 °C
Service Temperature	- 40 to +95 °C

\* equivalent to vertical exposure in Mid-European climate

#### Warranty

iSee2 warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user stores the material in the original boxes (out of direct sunlight) from our factory. We also recommend to store our material at 21°C with 50% relative humidity. iSee2 only warrants our products to be free from defects in workmanship or defects in iSee2 material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise shall be assumed by the seller or manufacturer. User assumes all risk and liability in connection herewith. All data values quoted above are typical and should not be used to deem the product defective, if measured values are different