



ATC SERIES

COLOUR-STABLE DYED FILM

Get a standout look, on-the-road privacy, and a nice upgrade in glass performance with the LLumar® ATC Series. This film is dyed all the way through for a cool charcoal hue that stays true and stands up to the test of time.

- Good heat rejection
- More than 99% UV protection*
- Enhanced style
- Increased privacy for passengers and belongings
- Variety of shades from light to dark
- Charcoal colour matches factory-installed privacy glass
- Scratch-resistant coating helps protect against damage
- Enhanced protection from shattered glass
- Manufacturer's 7 year limited warranty**

* Wavelengths 300-380nm

** Certain restrictions apply; see a dealer for details.

ATC SERIES

ATC 05 CH SR HPR (Charcoal)

Performance Data

% Visible Light Transmission	5
------------------------------	---

% Total Solar Energy Rejection	44
--------------------------------	----

% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	22
--	----

% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	29
---	----

% Ultraviolet Protection (wavelengths 300-380nm)	>99
---	-----

% Glare Reduction	94
-------------------	----

% Visible Light Reflection (exterior)	5
--	---



ATC SERIES

ATC 15 CH SR HPR (Charcoal)

Performance Data

% Visible Light Transmission	18
% Total Solar Energy Rejection	40
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	22
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	29
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	79
% Visible Light Reflection (exterior)	5

ATC SERIES

ATC 20 CH SR HPR (Charcoal)

Performance Data	
% Visible Light Transmission	25
% Total Solar Energy Rejection	38
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	22
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	29
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	72
% Visible Light Reflection (exterior)	6



ATC SERIES

ATC 35 CH SR HPR (Charcoal)

Performance Data

% Visible Light Transmission	38
------------------------------	----

% Total Solar Energy Rejection	35
--------------------------------	----

% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	22
--	----

% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	29
---	----

% Ultraviolet Protection (wavelengths 300-380nm)	>99
---	-----

% Glare Reduction	57
-------------------	----

% Visible Light Reflection (exterior)	6
--	---



ATC SERIES

ATC 50 CH SR HPR (Charcoal)

Performance Data

% Visible Light Transmission	60
% Total Solar Energy Rejection	28
% IR Energy Rejection (IRER) (wavelengths 780-2500nm)	22
% Selective IR Rejection (SIRR) (wavelengths 780-2500nm)	28
% Ultraviolet Protection (wavelengths 300-380nm)	>99
% Glare Reduction	32
% Visible Light Reflection (exterior)	7